

GRS-4022 DP/DT Maintained Parts List

Item #	Circuitry	Switch Function	Electrical Rating	Actuator Color	Actuator Legend & Color	Housing Color	Terminal Style	Insulation Barriers Between Poles
<u>GRS-4022-0000</u>	DPDT	ON-ON	13A @ 125 VAC 10A @ 250 VAC ½ HP @ 125-250 VAC 5A @ 14V (T)	Black	None	Black	Quick Connect .187" x.032"	Yes
<u>GRS-4022-0001</u>	DPDT	ON-ON	8A @ 125 VAC 4A @ 250 VAC 3A @ 277 VAC	Black	None	Black	Quick Connect .187" x.032"	Yes
<u>GRS-4022-0003</u>	DPDT	ON-ON	16A @ 125-250 VAC 10A @ 14V (T) 3A @ 125 V (L) ¾ HP @ 125-250 VAC 10 (4) 250~µ T 85°	Black	I/O Horizontal White	Black	Quick Connect .187" x.032"	Yes
<u>GRS-4022-0013</u>	DPDT	ON-ON	16A @ 125-250 VAC 10A @ 14V (T) 3A @ 125 V (L) ¾ HP @ 125-250 VAC 10 (4) 250~µ T 85°	Black	I/O Vertical White	Black	Quick Connect .187" x.032"	Yes
<u>GRS-4022-0021</u>	DPDT	ON-ON	16A @ 125-250 VAC 10A @ 14V (T) 3A @ 125 V (L) ¾ HP @ 125-250 VAC 10 (4) 250~µ T 85°	Black	I/O Vertical White	Black	Solder .110" x.032"	Yes
<u>GRS-4022-1600</u>	DPDT	ON-ON	16A @ 125-250 VAC 10A @ 14V (T) 3A @ 125 V (L) ¾ HP @ 125-250 VAC 10 (4) 250~µ T 85°	Black	None	Black	Quick Connect .187" x.032"	Yes