





THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.

Rating	12(4)A 250VAC			Mounting Hole	Circuit
Contact Resistance	50m ohm Max.				
Insulation Resistance	DC 500V 100M ohm Min.				
Dielectric Strength	AC 1500V 1 minute				
Function	6P DPDT ON-OFF-ON				
Operation Temp.	0° C ~ 85° C				


MATERIAL:

Frame: Nylon 6/6, Black
UL Flame: 94-V0

Lever: Metal

Terminal: Copper Alloy

Water proof and Dust Proof
to fit IP-56



Series		Lever Type		Std.	
GTS448	E	1	01	AHR	Knurl Nut
Function				Hex Nut	
Term. Type .250" SQ					
No Barrier					

Tolerances Unless Otherwise Specified +/-0.5.

RoHS Compliant

R13-448E1-01A-HR

7 Updated Order Chart, SCI part number & CWI logo APhilip 02/06/23

6 Updated views, Materials & Dimensions. 3-06-13.

CW INDUSTRIES
Southampton, Pa. 18966
Tel 215.355.7080/www.cwind.com

Date Drawn: 1/28/11

Rev. 7

Unit: mm

Checked By: *G. Guld*

Title: **TOGGLE SWITCH**

CW P/N: **GTS448E101AHR**